

Description

Fastener Length: 0-63/64", Thread: 6-32, Head Width: 7/64", Thread Length: 31/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2126253
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-833-8966
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21262-53 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.923 Inches Minimum And 0.969 Inches Maximum
Fastener Length:	0.985 Inches Minimum And 1.031 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Q-p-416 Type 2 Class 3 Fed Spec 13th Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21262-53> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.