

Description

Fastener Length: 0-63/64", Thread: 1/4-28, Head Width: 3/16", Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2126256
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-456-6761
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21262-56 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.914 Inches Minimum And 1.031 Inches Maximum
Fastener Length:	0.985 Inches Minimum And 1.031 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Locking Feature:	Pellet Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.188 Inches Minimum And 0.190 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21262-56> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.