

**Description**

Fastener Length: 5/16", Thread: 8-32, Head Width: 9/64", Thread Length: 5/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS212629                                  |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5305-00-855-3605                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS21262-9 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.265 Inches Minimum And 0.327 Inches Maximum                       |
| <b>Fastener Length:</b>                      | 0.297 Inches Minimum And 0.327 Inches Maximum                       |
| <b>Head Style:</b>                           | Flat Chamfer  |
| <b>Head Diameter:</b>                        | 0.262 Inches Minimum And 0.270 Inches Maximum                       |
| <b>Head Height:</b>                          | 0.159 Inches Minimum And 0.164 Inches Maximum                       |
| <b>Locking Feature:</b>                      | Strip Threads   |
| <b>Internal Drive Style:</b>                 | Hexagon   |
| <b>Nominal Thread Diameter:</b>              | 0.164 Inches  |
| <b>Width Across Flats:</b>                   | 0.140 Inches Minimum And 0.142 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>             | 32  |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                      | 36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| <b>Minimum Yield Strength:</b>               | 130000 Pounds Per Square Inch                                       |
| <b>Material:</b>                             | Steel Overall   |
| <b>Material Document And Classification:</b> | 66 Fed Std Single Material Response Overall                         |
| <b>Surface Treatment:</b>                    | Cadmium Overall And Chromate Overall                                |
| <b>Thread Series Designator:</b>             | Unc   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21262-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.