

## Description

Length: 12.75", sheet thickness: 0.52"-0.85", Teflon per AMS 3652 and ASTM D4895, MS21266 series grommet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

### Alternate Part Numbers

[STC21266-2T](#) [BACG20Z-N](#) [BACG20Z-B](#)

SKU / Model:	MS212662T
Minimum Qty (MOQ):	5
NSN:	5325-00-901-0804
Schedule B:	4016.93.0090
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



\* See page 2 for technical characteristics

## P/N MS21266-2T Specifications

<b>Groove Depth:</b>	0.100 Inches Nominal
<b>Groove Width:</b>	0.090 Inches Nominal
<b>Overall Height:</b>	0.175 Inches Nominal
<b>Overall Width:</b>	0.155 Inches Nominal
<b>Tab Width:</b>	0.067 Inches Nominal
<b>Grommet Style:</b>	Edging
<b>Width Between Tabs:</b>	0.067 Inches Nominal
<b>Grommet Construction Type:</b>	Split
<b>Grommet Overall Length:</b>	12.620 Inches Minimum And 19.000 Inches Maximum
<b>Color:</b>	Any Acceptable Overall
<b>Material:</b>	Plastic Polytetrafluoroethylene Overall

## How to Order

Order this nonmetallic grommet from our inventory online by visiting <https://military-fasteners.com/grommets/nonmetallic+grommets/MS21266-2T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.