

### P/N MS21266-5T

### **Description**

Length: 12.75", sheet thickness: .192"-.255", Teflon per AMS 3652 and ASTM D4895, MS21266 series grommet

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

# Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

STC21266-5T BACG02Z-R BACG20Z-E

SKU / Model:	MS212665T
Minimum Qty (MOQ):	2
NSN:	5325-01-072-9243
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



<sup>\*</sup> See page 2 for technical characteristics

## **P/N MS21266-5T Specifications**

Groove Depth:	0.170 Inches Nominal
Groove Width:	0.260 Inches Nominal
Overall Height:	0.385 Inches Nominal
Overall Width:	0.240 Inches Nominal
Tab Width:	0.057 Inches Minimum And 0.072 Inches Maximum
Grommet Style:	Edging
Width Between Tabs:	0.057 Inches Minimum And 0.072 Inches Maximum
Grommet Construction Type:	Split
Grommet Overall Length:	12.620 Inches Minimum And 19.000 Inches Maximum
Color:	Gray, Light Overall
Material:	Plastic Polytetrafluoroethylene Overall
Material Document And Classification:	Ams 3651 Assn Std Single Material Response Overall

## **How to Order**

Order this nonmetallic grommet from our inventory online by visiting <a href="https://military-fasteners.com/grommets/nonmetallic+grommets/MS21266-5T">https://military-fasteners.com/grommets/nonmetallic+grommets/MS21266-5T</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/grommets/nonmetallic+grommets/MS21266-5T">https://military-fasteners.com/grommets/nonmetallic+grommets/MS21266-5T</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/grommets/nonmetallic+grommets/MS21266-5T">https://military-fasteners.com/grommets/nonmetallic+grommets/MS21266-5T</a> and selecting the