

**Description**

Length: 12.75", sheet thickness: .380"-.510", Teflon per AMS 3652 and ASTM D4895, MS21266 series grommet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[STC21266-8T](#) [BACG20Z-U](#) [BACG20Z-H](#)

SKU / Model:	MS212668T
Minimum Qty (MOQ):	2
NSN:	5325-01-058-8912
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



\* See page 2 for technical characteristics

## P/N MS21266-8T Specifications

<b>Groove Depth:</b>	0.175 Inches Minimum And 0.185 Inches Maximum
<b>Groove Width:</b>	0.510 Inches Minimum And 0.520 Inches Maximum
<b>Overall Height:</b>	0.635 Inches Minimum And 0.645 Inches Maximum
<b>Overall Width:</b>	0.250 Inches Minimum And 0.260 Inches Maximum
<b>Tab Width:</b>	0.062 Inches Minimum And 0.072 Inches Maximum
<b>Grommet Style:</b>	Edging
<b>Width Between Tabs:</b>	0.062 Inches Minimum And 0.072 Inches Maximum
<b>Grommet Construction Type:</b>	Split
<b>Grommet Overall Length:</b>	12.620 Inches Minimum And 12.750 Inches Maximum
<b>Color:</b>	Any Acceptable Overall
<b>Material:</b>	Plastic Polytetrafluoroethylene Overall
<b>Material Document And Classification:</b>	Ams-3651 Assn Std Single Material Response Overall

## How to Order

Order this nonmetallic grommet from our inventory online by visiting <https://military-fasteners.com/grommets/nonmetallic+grommets/MS21266-8T> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.