Military-Fasteners.com

P/N MS21266-8T

Description

Length: 12.75", sheet thickness: .380"-.510", Teflon per AMS 3652 and ASTM D4895, MS21266 series grommet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

STC21266-8T BACG20Z-U BACG20Z-H

SKU / Model:	MS212668T
Minimum Qty (MOQ):	2
NSN:	5325-01-058-8912
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

* See page 2 for technical characteristics

P/N MS21266-8T Specifications

Groove Depth:	0.175 Inches Minimum And 0.185 Inches Maximum
Groove Width:	0.510 Inches Minimum And 0.520 Inches Maximum
Overall Height:	0.635 Inches Minimum And 0.645 Inches Maximum
Overall Width:	0.250 Inches Minimum And 0.260 Inches Maximum
Tab Width:	0.062 Inches Minimum And 0.072 Inches Maximum
Grommet Style:	Edging
Width Between Tabs:	0.062 Inches Minimum And 0.072 Inches Maximum
Grommet Construction Type:	Split
Grommet Overall Length:	12.620 Inches Minimum And 12.750 Inches Maximum
Color:	Any Acceptable Overall
Material:	Plastic Polytetrafluoroethylene Overall
Material Document And Classification:	Ams-3651 Assn Std Single Material Response Overall

How to Order

Order this nonmetallic grommet from our inventory online by visiting https://military-fasteners.com/grommets/nonmetallic+grommets/MS21266-8T and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.