

P/N MS21288-09

Military-Fasteners.com

Description

Fastener Length: 11/16", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 41/64"

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	MS2128809
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-944-2636
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21288-09 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.626 Inches Minimum And 0.686 Inches Maximum
Fastener Length:	0.688 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.260 Inches Nominal
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.040 Inches Minimum And 0.050 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/MS21288-09</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.