

Description

Fastener Length: 5/16", Thread: 10-32, Head Width: 5/32", Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2129510 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-849-8164 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS21295-10 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.265 Inches Minimum And 0.327 Inches Maximum |
| Fastener Length: | 0.297 Inches Minimum And 0.327 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.303 Inches Minimum And 0.312 Inches Maximum |
| Head Height: | 0.185 Inches Minimum And 0.190 Inches Maximum |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.190 Inches |
| Width Across Flats: | 0.156 Inches Minimum And 0.158 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Hardness Rating: | 80.0 Rockwell B Minimum Overall |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Material: | Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21295-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.