

Description

Fastener Length: 25/64", Thread: 4-40, Head Width: 3/32", Thread Length: 25/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2129513 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-456-0001 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21295-13 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.310 Inches Minimum And 0.390 Inches Maximum |
| Fastener Length: | 0.360 Inches Minimum And 0.390 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.176 Inches Minimum And 0.183 Inches Maximum |
| Head Height: | 0.108 Inches Minimum And 0.112 Inches Maximum |
| Locking Feature: | Strip Threads |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.112 Inches |
| Width Across Flats: | 0.094 Inches Minimum And 0.095 Inches Maximum |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Hardness Rating: | 80.0 Rockwell B Minimum Overall |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Material: | Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 305 Overall Or Steel Comp 316 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 6 Type |
| Departure From Cited Designator: | As Modified By Locking Feature |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21295-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.