

Description

Fastener Length: 7/16", Thread: 6-32, Head Width: 7/64", Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2129520
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-913-6140
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21295-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.350 Inches Minimum And 0.390 Inches Maximum
Fastener Length:	0.412 Inches Minimum And 0.452 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.225 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21295-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.