

Description

Fastener Length: 7/8", Thread: 3/8-24, Head Width: 5/16", Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2129552 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-00-841-2083 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21295-52 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.807 Inches Minimum And 0.890 Inches Maximum |
| Fastener Length: | 0.860 Inches Minimum And 0.890 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.550 Inches Minimum And 0.562 Inches Maximum |
| Head Height: | 0.368 Inches Minimum And 0.375 Inches Maximum |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.375 Inches |
| Width Across Flats: | 0.312 Inches Minimum And 0.316 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Hardness Rating: | 80.0 Rockwell B Minimum Overall |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Material: | Plastic Locking Feature |
| Material: | Steel Comp 302 Fastener Or Steel Comp 303 Fastener Or Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener |
| Material Document And Classification: | 66 Fed Std All Material Responses Fastener |
| Surface Treatment: | Passivate Fastener |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Fastener |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21295-52> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.