

**Description**

Fastener Length: 7/8", Thread: 3/8-24, Head Width: 5/16", Thread Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS2129552
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-841-2083
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS21295-52 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.807 Inches Minimum And 0.890 Inches Maximum
<b>Fastener Length:</b>	0.860 Inches Minimum And 0.890 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.550 Inches Minimum And 0.562 Inches Maximum
<b>Head Height:</b>	0.368 Inches Minimum And 0.375 Inches Maximum
<b>Locking Feature:</b>	Patch Threads Or Pellet Threads Or Strip Threads
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Width Across Flats:</b>	0.312 Inches Minimum And 0.316 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Hardness Rating:</b>	80.0 Rockwell B Minimum Overall
<b>Minimum Yield Strength:</b>	30000 Pounds Per Square Inch
<b>Material:</b>	Plastic Locking Feature
<b>Material:</b>	Steel Comp 302 Fastener Or Steel Comp 303 Fastener Or Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Fastener
<b>Surface Treatment:</b>	Passivate Fastener
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Fastener
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21295-52> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.