

Description

Fastener Length: 1", Thread: 6-32, Head Width: 7/64", Thread Length: 3/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2129553 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-00-060-9741 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS21295-53 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.750 Inches Minimum |
| Fastener Length: | 1.000 Inches Nominal |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.218 Inches Minimum And 0.226 Inches Maximum |
| Head Height: | 0.134 Inches Minimum And 0.138 Inches Maximum |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.138 Inches |
| Width Across Flats: | 0.109 Inches Minimum And 0.111 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 80.0 Rockwell B Nominal Overall |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unc |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21295-53> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.