

P/N MS21295-8

Description

Fastener Length: 5/16", Thread: 6-32, Head Width: 7/64", Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS212958

Minimum Qty (MOQ): 10 EA

NSN: 5305-00-912-5836

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21295-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.235 Inches Minimum And 0.265 Inches Maximum
Fastener Length:	0.297 Inches Minimum And 0.327 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Minimum And 0.111 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell B Minimum Overall
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unc

How to Order

Order this screwlock from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/MS21295-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.