

Description

Fastener Length: 5/16", Thread: 6-32, Head Width: 9/64", Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS212959
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-934-9729
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N MS21295-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.235 Inches Minimum And 0.327 Inches Maximum
Fastener Length:	0.297 Inches Minimum And 0.327 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.262 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.159 Inches Minimum And 0.164 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.141 Inches Minimum And 0.144 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	8000 Pounds Per Square Inch
Hardness Rating:	80.0 Rockwell C Minimum Fastener
Minimum Yield Strength:	30000 Pounds Per Square Inch
Material:	Plastic Polyamide Locking Feature
Material:	Steel Comp 302 Fastener Or Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener Or Steel Comp 384 Fastener Or Steel Comp Xm-7 Fastener
Surface Treatment:	Passivate Fastener
Surface Treatment Document And Classification:	Stm A380 Assn Std Single Treatment Response Fastener
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	6 Type

How to Order

Order this screwlock from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21295-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.