

Description

Fastener Length: 5/16", Thread: 6-32, Head Width: 9/64", Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | MS212959 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-934-9729 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N MS21295-9 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.235 Inches Minimum And 0.327 Inches Maximum |
| Fastener Length: | 0.297 Inches Minimum And 0.327 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.262 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.159 Inches Minimum And 0.164 Inches Maximum |
| Locking Feature: | Patch Threads |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.138 Inches |
| Width Across Flats: | 0.141 Inches Minimum And 0.144 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 8000 Pounds Per Square Inch |
| Hardness Rating: | 80.0 Rockwell C Minimum Fastener |
| Minimum Yield Strength: | 30000 Pounds Per Square Inch |
| Material: | Plastic Polyamide Locking Feature |
| Material: | Steel Comp 302 Fastener Or Steel Comp 304 Fastener Or Steel Comp 305 Fastener Or Steel Comp 316 Fastener Or Steel Comp 384 Fastener Or Steel Comp Xm-7 Fastener |
| Surface Treatment: | Passivate Fastener |
| Surface Treatment Document And Classification: | Stm A380 Assn Std Single Treatment Response Fastener |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 6 Type |

How to Order

Order this screwlock from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21295-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.