

Description

Fastener Length: 1-33/64", Thread: 5/16-24, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2129605014
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-270-1716
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21296-05014 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.541 Inches Minimum And 0.674 Inches Maximum
Fastener Length:	1.509 Inches Minimum And 1.539 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.237 Inches Minimum And 0.287 Inches Maximum
Extended Washer Diameter:	0.575 Inches Minimum And 0.585 Inches Maximum
Extended Washer Thickness:	0.035 Inches Minimum And 0.065 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Head Minor Diameter:	0.360 Inches Minimum And 0.375 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	260000 Pounds Per Square Inch
Hardness Rating:	51.0 Rockwell C Minimum Overall And 54.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Mil-c-8837 Ty2 Cl2 Fed Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS21296-05014> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.