

Description

Fastener Length: 2-49/64", Thread: 9/16-18, Thread Length: 1-1/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2129609028 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-063-3787 |
| Schedule B: | 7318.15.2010 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS21296-09028 Specifications

| | |
|-----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.005 Inches Minimum And 1.055 Inches Maximum |
| Fastener Length: | 2.765 Inches Minimum And 2.795 Inches Maximum |
| Head Style: | Spline Extended Washer |
| Head Height: | 0.495 Inches Minimum And 0.515 Inches Maximum |
| Width Between Flats: | 0.610 Inches Minimum And 0.625 Inches Maximum |
| Extended Washer Diameter: | 1.037 Inches Minimum And 1.047 Inches Maximum |
| Extended Washer Thickness: | 0.071 Inches Minimum And 0.091 Inches Maximum |
| Grip Diameter: | 0.5605 Inches Minimum And 0.5615 Inches Maximum |
| Nominal Thread Diameter: | 0.562 Inches |
| Grip Length: | 1.740 Inches Minimum And 1.760 Inches Maximum |
| Thread Quantity Per Inch: | 18 |
| Hardness Rating: | 51.0 Rockwell C Minimum Overall And 54.0 Rockwell C Maximum Overall |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Material: | Steel Comp H11 Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS21296-09028> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.