

P/N MS21296-09028

Military-Fasteners.com

#### Description

Fastener Length: 2-49/64", Thread: 9/16-18, Thread Length: 1-1/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	MS2129609028
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-063-3787
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N MS21296-09028 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.005 Inches Minimum And 1.055 Inches Maximum
Fastener Length:	2.765 Inches Minimum And 2.795 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.495 Inches Minimum And 0.515 Inches Maximum
Width Between Flats:	0.610 Inches Minimum And 0.625 Inches Maximum
Extended Washer Diameter:	1.037 Inches Minimum And 1.047 Inches Maximum
Extended Washer Thickness:	0.071 Inches Minimum And 0.091 Inches Maximum
Grip Diameter:	0.5605 Inches Minimum And 0.5615 Inches Maximum
Nominal Thread Diameter:	0.562 Inches
Grip Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Thread Quantity Per Inch:	18
Hardness Rating:	51.0 Rockwell C Minimum Overall And 54.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Material:	Steel Comp H11 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/MS21296-09028</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.