

Description

Fastener Length: 4-31/64", Thread: 3/4-16, Thread Length: 1-19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2129612051
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-395-1233
Schedule B:	7318.15.8085
ECCN:	9A991



* See page 2 for technical characteristics

P/N MS21296-12051 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.293 Inches Nominal
Fastener Length:	4.481 Inches Minimum And 4.511 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.590 Inches Minimum And 0.610 Inches Maximum
Extended Washer Diameter:	1.384 Inches Minimum And 1.394 Inches Maximum
Extended Washer Thickness:	0.098 Inches Minimum And 0.118 Inches Maximum
Grip Diameter:	0.7480 Inches Minimum And 0.7490 Inches Maximum
Head Minor Diameter:	0.797 Inches Minimum And 0.812 Inches Maximum
End Item Identification:	Pacer Dawn
Nominal Thread Diameter:	0.750 Inches
Grip Length:	3.178 Inches Minimum And 3.198 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	103000 Pounds Per Square Inch
Hardness Rating:	51.0 Rockwell C Minimum Overall And 54.0 Rockwell C Maximum Overall
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Mil-c-8837,type II,class 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS21296-12051> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.