

**Description**

Fastener Length: 4-31/64", Thread: 3/4-16, Thread Length: 1-19/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS2129612051
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-395-1233
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N MS21296-12051 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.293 Inches Nominal
<b>Fastener Length:</b>	4.481 Inches Minimum And 4.511 Inches Maximum
<b>Head Style:</b>	Spline Extended Washer
<b>Head Height:</b>	0.590 Inches Minimum And 0.610 Inches Maximum
<b>Extended Washer Diameter:</b>	1.384 Inches Minimum And 1.394 Inches Maximum
<b>Extended Washer Thickness:</b>	0.098 Inches Minimum And 0.118 Inches Maximum
<b>Grip Diameter:</b>	0.7480 Inches Minimum And 0.7490 Inches Maximum
<b>Head Minor Diameter:</b>	0.797 Inches Minimum And 0.812 Inches Maximum
<b>End Item Identification:</b>	Pacer Dawn
<b>Nominal Thread Diameter:</b>	0.750 Inches
<b>Grip Length:</b>	3.178 Inches Minimum And 3.198 Inches Maximum
<b>Thread Quantity Per Inch:</b>	16
<b>Minimum Tensile Strength:</b>	103000 Pounds Per Square Inch
<b>Hardness Rating:</b>	51.0 Rockwell C Minimum Overall And 54.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp H11 Overall
<b>Material Document And Classification:</b>	Ams 6487 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-8837,type li,class 2 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS21296-12051> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.