

Description

Fastener Length: 2-27/64", Hole Diameter: 1/64", Thread: 3/8-24, Thread Length: 47/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21296H06027
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-532-4203
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N MS21296H06027 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.734 Inches Nominal
Fastener Length:	2.407 Inches Minimum And 2.437 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.327 Inches Minimum And 0.347 Inches Maximum
Extended Washer Diameter:	0.691 Inches Minimum And 0.701 Inches Maximum
Extended Washer Thickness:	0.044 Inches Minimum And 0.064 Inches Maximum
Hole Diameter:	0.005 Inches Nominal
Grip Diameter:	0.373 Inches Minimum And 0.374 Inches Maximum
Head Minor Diameter:	0.422 Inches Minimum And 0.438 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.688 Inches Nominal
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	260000 Pounds Per Square Inch
Hole Configuration Style:	Round
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Mil-c-8837, Ty II, Cl2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas-21296 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21296H06027> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.