

Description

Fastener Length: 2-11/32", Hole Diameter: ", Thread: 7/16-20, Thread Length: 53/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS21296H07024 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-056-0152 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS21296H07024 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.823 Inches Minimum And 0.873 Inches Maximum |
| Fastener Length: | 2.333 Inches Minimum And 2.363 Inches Maximum |
| Head Style: | Spline Extended Washer |
| Head Height: | 0.310 Inches Minimum And 0.350 Inches Maximum |
| Width Between Flats: | 0.514 Inches Minimum And 0.521 Inches Maximum |
| Extended Washer Diameter: | 0.807 Inches Minimum And 0.817 Inches Maximum |
| Extended Washer Thickness: | 0.053 Inches Minimum And 0.073 Inches Maximum |
| Hole Diameter: | 0.050 Inches Minimum And 0.060 Inches Maximum |
| Grip Diameter: | 0.4360 Inches Minimum And 0.4370 Inches Maximum |
| Nominal Thread Diameter: | 0.438 Inches |
| Grip Length: | 1.490 Inches Minimum And 1.510 Inches Maximum |
| Hole Quantity: | 4 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 260000 Pounds Per Square Inch |
| Hardness Rating: | 51.0 Rockwell C Minimum Overall And 54.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Round Longitudinal Hole |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Material: | Steel Comp H11 Overall |
| Material Document And Classification: | Ams 6487 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Mil-s-8837 Ty 2 Cl 2 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21296H07024> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.