

**Description**

Fastener Length: 1-3/8", Hole Diameter: ", Thread: 1/4-28, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21297H04014
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-385-9856
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS21297H04014 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.495 Inches Nominal
<b>Fastener Length:</b>	1.370 Inches Minimum And 1.400 Inches Maximum
<b>Head Style:</b>	Spline Extended Washer
<b>Head Height:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Extended Washer Diameter:</b>	0.026 Inches Minimum And 0.046 Inches Maximum
<b>Extended Washer Thickness:</b>	0.026 Inches Minimum And 0.046 Inches Maximum
<b>Hole Diameter:</b>	0.050 Inches Minimum And 0.060 Inches Maximum
<b>Grip Diameter:</b>	0.2485 Inches Minimum And 0.2495 Inches Maximum
<b>Head Minor Diameter:</b>	0.235 Inches Minimum And 0.250 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.865 Inches Minimum And 0.885 Inches Maximum
<b>Hole Quantity:</b>	4
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	220000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Spline
<b>Material:</b>	Steel Comp H11 Overall
<b>Material Document And Classification:</b>	Ams 6487 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-8837,ty2 Cl2 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21297H04014> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.