



Military-Fasteners.com

P/N MS21297H04014

Description

Fastener Length: 1-3/8", Hole Diameter: ", Thread: 1/4-28, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21297H04014
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-385-9856
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21297H04014 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.495 Inches Nominal
Fastener Length:	1.370 Inches Minimum And 1.400 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.240 Inches Minimum And 0.260 Inches Maximum
Extended Washer Diameter:	0.026 Inches Minimum And 0.046 Inches Maximum
Extended Washer Thickness:	0.026 Inches Minimum And 0.046 Inches Maximum
Hole Diameter:	0.050 Inches Minimum And 0.060 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Head Minor Diameter:	0.235 Inches Minimum And 0.250 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hole Configuration Style:	Spline
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Mil-c-8837,ty2 Cl2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21297H04014> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.