

## P/N MS21297H05013

### **Description**

Fastener Length: 1-13/32", Hole Diameter: ", Thread: 5/16-24, Thread Length: 39/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS21297H05013
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-334-7915
Schedule B:	7318.15.8085
ECCN:	9A991



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21297H05013 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.596 Inches Nominal
Fastener Length:	1.401 Inches Minimum And 1.431 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.302 Inches Minimum And 0.322 Inches Maximum
Extended Washer Diameter:	0.580 Inches Nominal
Extended Washer Thickness:	0.035 Inches Minimum And 0.055 Inches Maximum
Hole Diameter:	0.050 Inches Minimum And 0.060 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Head Minor Diameter:	0.360 Inches Minimum And 0.375 Inches Maximum
End Item Identification:	Pacer Dawn
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Hardness Rating:	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
Hole Configuration Style:	Spline
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Special Features:	Hole Drilled In Top Center Of Head,0.185/0.225 In. Dia X 0.118 In. Nomdeep
Material:	Steel Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Mil-c-8837,type li,class 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

# **How to Order**

