

Description

Fastener Length: 3-1/64", Hole Diameter: ", Thread: 7/16-20, Thread Length: 49/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21297H07036
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-385-9831
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21297H07036 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.763 Inches Nominal
Fastener Length:	3.013 Inches Minimum And 3.043 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.383 Inches Minimum And 0.403 Inches Maximum
Extended Washer Diameter:	0.807 Inches Minimum And 0.817 Inches Maximum
Extended Washer Thickness:	0.053 Inches Minimum And 0.073 Inches Maximum
Hole Diameter:	0.050 Inches Minimum And 0.060 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Head Minor Diameter:	0.485 Inches Minimum And 0.500 Inches Maximum
Nominal Thread Diameter:	0.437 Inches
Grip Length:	2.240 Inches Minimum And 2.260 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hole Configuration Style:	Spline
Material:	Steel Comp H11 Overall
Material Document And Classification:	Ams 6487 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Mil-c-8837 Ty2 Cl2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21297H07036> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.