

Description

Fastener Length: 2-1/64", Thread: 5/8-18, Thread Length: 0-65/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21297H10016
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-058-3319
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS21297H10016 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.995 Inches Minimum And 1.045 Inches Maximum
Fastener Length:	2.005 Inches Minimum And 2.035 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.552 Inches Minimum And 0.572 Inches Maximum
Extended Washer Diameter:	1.153 Inches Minimum And 1.163 Inches Maximum
Extended Washer Thickness:	0.080 Inches Minimum And 0.100 Inches Maximum
Grip Diameter:	0.6230 Inches Minimum And 0.6240 Inches Maximum
Head Minor Diameter:	0.673 Inches Minimum And 0.688 Inches Maximum
Nominal Thread Diameter:	0.625 Inches
Grip Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hardness Rating:	46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall
Material:	Steel Comp H11 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21297H10016> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.