

Description

Fastener Length: 2-1/64", Thread: 5/8-18, Thread Length: 0-65/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS21297H10016 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-058-3319 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS21297H10016 Specifications

| | |
|-----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.995 Inches Minimum And 1.045 Inches Maximum |
| Fastener Length: | 2.005 Inches Minimum And 2.035 Inches Maximum |
| Head Style: | Spline Extended Washer |
| Head Height: | 0.552 Inches Minimum And 0.572 Inches Maximum |
| Extended Washer Diameter: | 1.153 Inches Minimum And 1.163 Inches Maximum |
| Extended Washer Thickness: | 0.080 Inches Minimum And 0.100 Inches Maximum |
| Grip Diameter: | 0.6230 Inches Minimum And 0.6240 Inches Maximum |
| Head Minor Diameter: | 0.673 Inches Minimum And 0.688 Inches Maximum |
| Nominal Thread Diameter: | 0.625 Inches |
| Grip Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 220000 Pounds Per Square Inch |
| Hardness Rating: | 46.0 Rockwell C Minimum Overall And 50.0 Rockwell C Maximum Overall |
| Material: | Steel Comp H11 Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21297H10016> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.