



★ FASTENERS

Military-Fasteners.com

P/N MS21299-12

Description

Hole Diameter: 3/4", Diameter: 1-3/8", MS21299 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2129912 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5310-01-202-2703 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



* See page 2 for technical characteristics

P/N MS21299-12 Specifications

| | |
|--|---|
| Cross-sectional Shape Style: | Rectangular |
| Hole Diameter: | 0.752 Inches Minimum And 0.756 Inches Maximum |
| Peripheral Shape Style: | Round |
| Center Hole Shape Style: | 1 Round |
| Thickness: | 0.052 Inches Minimum And 0.072 Inches Maximum |
| Overall Diameter: | 1.423 Inches Minimum And 1.433 Inches Maximum |
| Hardness Rating: | 39.0 Rockwell C Minimum And 45.0 Rockwell C Maximum |
| Material: | Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-18729 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS21299-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.