

Description

Hole Diameter: 3/8", Diameter: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS212995K
Minimum Qty (MOQ):	50
NSN:	5310-01-475-3400
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21299-5K Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.314 Inches Minimum And 0.318 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.052 Inches Minimum And 0.072 Inches Maximum
Overall Diameter:	0.588 Inches Minimum And 0.598 Inches Maximum
Hardness Rating:	35.0 Rockwell C Minimum And 42.0 Rockwell C Maximum
Surface Finish:	125.0 Microinches All Surfaces
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams 5604,17-4ph,cond H 1025 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas-21299 Professional/Industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS21299-5K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.