

Description

MS21299C3 Flat Washer

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS21299C3](#)

SKU / Model:	MS21299C3
Minimum Qty (MOQ):	50
NSN:	5310-01-121-8526
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



P/N MS21299-C3 Specifications

Hole Diameter:	0.191 Inches Minimum And 0.195 Inches Maximum
Outside Diameter:	0.377 Inches Minimum And 0.387 Inches Maximum
Recess Diameter:	0.280 Inches Minimum And 0.290 Inches Maximum
Material Thickness:	0.067 Inches Minimum And 0.069 Inches Maximum
Hardness Rating:	39.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Recess Angle:	90.0 Degrees Nominal
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-18729 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS21299-C3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.