

P/N MS21299-C8

Military-Fasteners.com

Description

Hole Diameter: 1/2", MS21299 series washer

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | MS21299C8 |
|-------------------------|---|
| Minimum Qty (MOQ): | 50 |
| NSN: | 5310-01-119-6796 |
| Schedule B: | 7318.22.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



P/N MS21299-C8 Specifications

| Hole Diameter: | 0.501 Inches Minimum And 0.505 Inches Maximum |
|--|---|
| Outside Diameter: | 0.940 Inches Minimum And 0.950 Inches Maximum |
| Recess Diameter: | 0.622 Inches Minimum And 0.632 Inches Maximum |
| Material Thickness: | 0.071 Inches Minimum And 0.085 Inches Maximum |
| Hardness Rating: | 39.0 Rockwell C Minimum And 45.0 Rockwell C Maximum |
| Recess Angle: | 89.0 Degrees Minimum And 91.0 Degrees Maximum |
| Material: | Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-18729 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | 15 Recessed |

How to Order

Order this flat washer from our inventory online by visiting <u>https://military-fasteners.com/washers/flat+washers/MS21299-C8</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.