

Description

Hole Diameter: 5/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS21299C10K |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-01-573-7816 |
| ECCN: | EAR99 |
| National Motor Freight: | 097510, Washers I / S Chromium / Nickel Plated |



* See page 2 for technical characteristics

P/N MS21299C10K Specifications

| | |
|---|---|
| Hole Diameter: | 0.627 Inches Minimum And 0.631 Inches Maximum |
| Outside Diameter: | 1.182 Inches Minimum And 1.192 Inches Maximum |
| Recess Diameter: | 0.778 Inches Minimum And 0.788 Inches Maximum |
| Material Thickness: | 0.071 Inches Minimum And 0.085 Inches Maximum |
| Hardness Rating: | 35.0 Rockwell C Minimum And 42.0 Rockwell C Maximum |
| Recess Angle: | 90.0 Degrees Nominal |
| Part Name Assigned By Controlling Agency: | Washer Recessed |
| Material: | Steel Comp 630 Overall |
| Surface Treatment: | Passivate Overall |
| Style Designator: | 15 Recessed |

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS21299C10K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.