

**Description**

Hole Diameter: 3/4",

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21299C12K
Minimum Qty (MOQ):	10
NSN:	5310-01-477-5024
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



## P/N MS21299C12K Specifications

<b>Hole Diameter:</b>	0.752 Inches Minimum And 0.756 Inches Maximum
<b>Outside Diameter:</b>	1.423 Inches Minimum And 1.433 Inches Maximum
<b>Recess Diameter:</b>	0.903 Inches Minimum And 0.913 Inches Maximum
<b>Material Thickness:</b>	0.071 Inches Minimum And 0.085 Inches Maximum
<b>Hardness Rating:</b>	35.0 Rockwell C Minimum And 42.0 Rockwell C Maximum
<b>Recess Angle:</b>	90.0 Degrees Nominal
<b>Surface Finish:</b>	125.0 Microinches All Surfaces
<b>Material:</b>	Steel Comp 630 Overall
<b>Material Document And Classification:</b>	Ams 5604,17-4ph,cond H 1025 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	15 Recessed
<b>Specification/standard Data:</b>	80205-nas-21299 Professional/Industrial Association Standard

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS21299C12K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.