

Description

Hole Diameter: 3/16", MS21299 series washer

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS21299C3K |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5310-01-483-0361 |
| ECCN: | EAR99 |
| National Motor Freight: | 194130, Washers / Gaskets / Maint I / C Eng |



P/N MS21299C3K Specifications

| | |
|---|--|
| Hole Diameter: | 0.191 Inches Minimum And 0.195 Inches Maximum |
| Outside Diameter: | 0.377 Inches Minimum And 0.387 Inches Maximum |
| Recess Diameter: | 0.280 Inches Minimum And 0.290 Inches Maximum |
| Material Thickness: | 0.057 Inches Minimum And 0.069 Inches Maximum |
| End Item Identification: | 1055-01-450-4243;launcher,rocket,armored Vehicle Mounted:multiple Launch Rocket System |
| Hardness Rating: | 35.0 Rockwell C Minimum And 42.0 Rockwell C Maximum |
| Recess Angle: | 90.0 Degrees Nominal |
| Surface Finish: | 125.0 Microinches All Surfaces |
| Material: | Steel Comp 630 Overall |
| Material Document And Classification: | Ams 5604,17-4ph Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Style Designator: | 15 Recessed |
| Specification/standard Data: | 80205-nas-21299 Professional/industrial Association Standard |

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS21299C3K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.