

Description

size: 1/4", countersunk, cadmium plated steel, MS21299 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS21299-C4](#)

| | |
|-------------------------|---|
| SKU / Model: | MS21299C4 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5310-01-008-6798 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



P/N MS21299C4 Specifications

| | |
|---|---|
| Hole Diameter: | 0.251 Inches Minimum And 0.255 Inches Maximum |
| Outside Diameter: | 0.481 Inches Minimum And 0.491 Inches Maximum |
| Recess Diameter: | 0.340 Inches Minimum And 0.350 Inches Maximum |
| Material Thickness: | 0.067 Inches Minimum And 0.069 Inches Maximum |
| Hardness Rating: | 39.0 Rockwell C Minimum And 45.0 Rockwell C Maximum |
| Recess Angle: | 90.0 Degrees Nominal |
| Material: | Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-18729 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,c1 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | 15 Recessed |

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS21299C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.