

**Description**

Hole Diameter: 1/4", recessed, steel, MS21299 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21299C4K
Minimum Qty (MOQ):	25
NSN:	5310-01-483-0360
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS21299C4K Specifications

<b>Hole Diameter:</b>	0.251 Inches Minimum And 0.255 Inches Maximum
<b>Outside Diameter:</b>	0.481 Inches Minimum And 0.491 Inches Maximum
<b>Recess Diameter:</b>	0.340 Inches Minimum And 0.350 Inches Maximum
<b>Material Thickness:</b>	0.057 Inches Minimum And 0.069 Inches Maximum
<b>End Item Identification:</b>	1055-01-450-4243;launcher,rocket,armored Vehicle Mounted:multiple Launch Rocket System
<b>Hardness Rating:</b>	35.0 Rockwell C Minimum And 42.0 Rockwell C Maximum
<b>Recess Angle:</b>	90.0 Degrees Nominal
<b>Surface Finish:</b>	125.0 Microinches All Surfaces
<b>Material:</b>	Steel Comp 630 Overall
<b>Material Document And Classification:</b>	Ams 5604,17-4ph Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	15 Recessed
<b>Specification/standard Data:</b>	80205-nas-21299 Professional/industrial Association Standard

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS21299C4K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.