

Description

size: 5/16", washer, countersunk, cadmium plated steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21299C5
Minimum Qty (MOQ):	100
NSN:	5310-01-011-3094
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE
AVAILABLE

P/N MS21299C5 Specifications

Hole Diameter:	0.314 Inches Minimum And 0.318 Inches Maximum
Outside Diameter:	0.588 Inches Minimum And 0.598 Inches Maximum
Recess Diameter:	0.402 Inches Minimum And 0.412 Inches Maximum
Material Thickness:	0.057 Inches Minimum And 0.069 Inches Maximum
Hardness Rating:	39.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Recess Angle:	90.0 Degrees Nominal
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-18729 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,c1 2 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS21299C5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.