

Description

Hole Diameter: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21299C6K
Minimum Qty (MOQ):	20
NSN:	5310-01-483-0355
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21299C6K Specifications

Hole Diameter:	0.376 Inches Minimum And 0.380 Inches Maximum
Outside Diameter:	0.702 Inches Minimum And 0.712 Inches Maximum
Recess Diameter:	0.497 Inches Minimum And 0.507 Inches Maximum
Material Thickness:	0.071 Inches Minimum And 0.085 Inches Maximum
End Item Identification:	1055-01-450-4243;launcher,rocket,armored Vehicle Mounted:multiple Launch Rocket System
Hardness Rating:	35.0 Rockwell C Minimum And 42.0 Rockwell C Maximum
Recess Angle:	90.0 Degrees Nominal
Surface Finish:	125.0 Microinches All Surfaces
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams 5604,17-4ph Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed
Specification/standard Data:	80205-nas-21299 Professional/industrial Association Standard

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS21299C6K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.