

**Description**

Hole Diameter: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS21299-C7](#)

SKU / Model:	MS21299C7
Minimum Qty (MOQ):	25
NSN:	5310-01-134-8752
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



## P/N MS21299C7 Specifications

<b>Hole Diameter:</b>	0.439 Inches Minimum And 0.443 Inches Maximum
<b>Outside Diameter:</b>	0.821 Inches Minimum And 0.831 Inches Maximum
<b>Recess Diameter:</b>	0.539 Inches Minimum And 0.569 Inches Maximum
<b>Material Thickness:</b>	0.071 Inches Minimum And 0.085 Inches Maximum
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
<b>Recess Angle:</b>	90.0 Degrees Nominal
<b>Material:</b>	Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec Single Material Response Overall And Mil-s-18729 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	15 Recessed

## How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS21299C7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.