

Description

Hole Diameter: 1/2", MS21299 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21299C8
Minimum Qty (MOQ):	50
NSN:	5310-01-119-6796
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N MS21299C8 Specifications

Hole Diameter:	0.501 Inches Minimum And 0.505 Inches Maximum
Outside Diameter:	0.940 Inches Minimum And 0.950 Inches Maximum
Recess Diameter:	0.622 Inches Minimum And 0.632 Inches Maximum
Material Thickness:	0.071 Inches Minimum And 0.085 Inches Maximum
Hardness Rating:	39.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Recess Angle:	89.0 Degrees Minimum And 91.0 Degrees Maximum
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-18729 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS21299C8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.