

Description

Hole Diameter: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS21299C9 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5310-01-505-3022 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS21299C9 Specifications

| | |
|--|---|
| Hole Diameter: | 0.564 Inches Minimum And 0.568 Inches Maximum |
| Outside Diameter: | 1.059 Inches Minimum And 1.069 Inches Maximum |
| Recess Diameter: | 0.684 Inches Minimum And 0.694 Inches Maximum |
| Material Thickness: | 0.071 Inches Minimum And 0.085 Inches Maximum |
| Hardness Rating: | 39.0 Rockwell C Minimum And 45.0 Rockwell C Maximum |
| Recess Angle: | 90.0 Degrees Nominal |
| Surface Finish: | 125.0 Microinches All Surfaces |
| Special Features: | Spec Calls This: Washer, Countersunk, For Use With Bolts And Nuts Up To And Including 260 Ksi Flu |
| Material: | Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-6758&jdamil-s-18729 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Type II, Class 2 Fed Spec All Treatment Responses Overall |
| Style Designator: | 15 Recessed |

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21299C9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.