

**Description**

Hole Diameter: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21299C9
Minimum Qty (MOQ):	25
NSN:	5310-01-505-3022
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS21299C9 Specifications

<b>Hole Diameter:</b>	0.564 Inches Minimum And 0.568 Inches Maximum
<b>Outside Diameter:</b>	1.059 Inches Minimum And 1.069 Inches Maximum
<b>Recess Diameter:</b>	0.684 Inches Minimum And 0.694 Inches Maximum
<b>Material Thickness:</b>	0.071 Inches Minimum And 0.085 Inches Maximum
<b>Hardness Rating:</b>	39.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
<b>Recess Angle:</b>	90.0 Degrees Nominal
<b>Surface Finish:</b>	125.0 Microinches All Surfaces
<b>Special Features:</b>	Spec Calls This: Washer, Countersunk, For Use With Bolts And Nuts Up To And Including 260 Ksi Flu
<b>Material:</b>	Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	Mil-s-6758&jdamil-s-18729 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type Ii, Class 2 Fed Spec All Treatment Responses Overall
<b>Style Designator:</b>	15 Recessed

## How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21299C9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.