

Description

Hole Diameter: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21299C9
Minimum Qty (MOQ):	25
NSN:	5310-01-505-3022
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21299C9 Specifications

Hole Diameter:	0.564 Inches Minimum And 0.568 Inches Maximum
Outside Diameter:	1.059 Inches Minimum And 1.069 Inches Maximum
Recess Diameter:	0.684 Inches Minimum And 0.694 Inches Maximum
Material Thickness:	0.071 Inches Minimum And 0.085 Inches Maximum
Hardness Rating:	39.0 Rockwell C Minimum And 45.0 Rockwell C Maximum
Recess Angle:	90.0 Degrees Nominal
Surface Finish:	125.0 Microinches All Surfaces
Special Features:	Spec Calls This: Washer, Countersunk, For Use With Bolts And Nuts Up To And Including 260 Ksi Flu
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6758&jdamil-s-18729 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Type II, Class 2 Fed Spec All Treatment Responses Overall
Style Designator:	15 Recessed

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21299C9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.