

P/N MS21318-1

Description

length: 1/8", diameter: .058", round head, cadmium plated carbon steel, MS21318 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information


SKU / Model: MS213181

Minimum Qty (MOQ): 100


NSN: 5305-00-253-5603

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N MS21318-1 Specifications

Fastener Length:	0.109 Inches Minimum And 0.141 Inches Maximum
Head Style:	Round
Head Diameter:	0.090 Inches Minimum And 0.099 Inches Maximum
Head Height:	0.026 Inches Minimum And 0.034 Inches Maximum
Pilot Diameter:	0.046 Inches Minimum And 0.049 Inches Maximum
Pilot Length:	0.047 Inches Nominal
End Item Identification:	Engine, Aircraft, F-108 (cfm-56, Kc-135a); Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Support Equipment, B-1 Aircraft; Test Consoles, Minisace; Trainer, B-1b Aircraft; Radar Set, An/tpn-18; Close In Weapon System (ciws-phalanx); Engine, Aircraft, Ge T-700 (uh-60a); Engine, Aircraft, T56-a-7/15 (c-130b/e/h/n/p)
Features Provided:	Casehardened
Nonmachine Thread Style:	Drive Screw (type U)
Nonmachine Nominal Thread Diameter:	0.058 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall

How to Order

Order this drive screw from our inventory online by visiting https://military-fasteners.com/screws/drive+screws/MS21318-1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.