

Description

length: 1/8", diameter: 0.098", round head, cadmium plated carbon steel, MS21318 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2131813
Minimum Qty (MOQ):	100
NSN:	5305-00-253-5609
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21318-13 Specifications

Fastener Length:	0.109 Inches Minimum And 0.141 Inches Maximum
Head Style:	Round
Head Diameter:	0.146 Inches Minimum And 0.162 Inches Maximum
Head Height:	0.059 Inches Minimum And 0.069 Inches Maximum
Pilot Diameter:	0.080 Inches Minimum And 0.083 Inches Maximum
Pilot Length:	0.047 Inches Nominal
End Item Identification:	Aircraft, (ac-130h, Mc-130h, Ec-0130e, Hc-130); Airborne Mobile Dir Air Spt Ctl (2id),(02m Jul83)(an/uyq-3a); Support Equipment, B-1 Aircraft; Missile, All-weather Anti-ship, Harpoon (agm-84); Compressor, Reciprocating M4; Radar Set, An/tpn-18; Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p); Close In Weapon System (ciws-phlanx); Aircraft, Awacs, E-3a; Engine, Aircraft Tf33-p-3/5/9 (c/ec-135, B-52h); Sturgeon Class Ssn (637)
Features Provided:	Casehardened
Nonmachine Thread Style:	Drive Screw (type U)
Nonmachine Nominal Thread Diameter:	0.098 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Nondefinitive Spec/std Data:	U Type

How to Order

Order this drive screw from our inventory online by visiting <https://military-fasteners.com/screws/drive+screws/MS21318-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.