

## Description

length: 1/8", diameter: 0.098", round head, cadmium plated carbon steel, MS21318 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS2131813
Minimum Qty (MOQ):	100
NSN:	5305-00-253-5609
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS21318-13 Specifications

<b>Fastener Length:</b>	0.109 Inches Minimum And 0.141 Inches Maximum
<b>Head Style:</b>	Round
<b>Head Diameter:</b>	0.146 Inches Minimum And 0.162 Inches Maximum
<b>Head Height:</b>	0.059 Inches Minimum And 0.069 Inches Maximum
<b>Pilot Diameter:</b>	0.080 Inches Minimum And 0.083 Inches Maximum
<b>Pilot Length:</b>	0.047 Inches Nominal
<b>End Item Identification:</b>	Aircraft, (ac-130h, Mc-130h, Ec-0130e, Hc-130); Airborne Mobile Dir Air Spt Ctl (2id),(02m Jul83)(an/uyq-3a); Support Equipment, B-1 Aircraft; Missile, All-weather Anti-ship, Harpoon (agm-84); Compressor, Reciprocating M4; Radar Set, An/tpn-18; Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p); Close In Weapon System (ciws-phlanx); Aircraft, Awacs, E-3a; Engine, Aircraft Tf33-p-3/5/9 (c/ec-135, B-52h); Sturgeon Class Ssn (637)
<b>Features Provided:</b>	Casehardened
<b>Nonmachine Thread Style:</b>	Drive Screw (type U)
<b>Nonmachine Nominal Thread Diameter:</b>	0.098 Inches
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
<b>Nondefinitive Spec/std Data:</b>	U Type

## How to Order

Order this drive screw from our inventory online by visiting <https://military-fasteners.com/screws/drive+screws/MS21318-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.