

Description

3/16" length, .114" diameter, round head, cadmium plated carbon steel, MS21318 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2131820
Minimum Qty (MOQ):	100
NSN:	5305-00-253-5614
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21318-20 Specifications

Fastener Length:	0.172 Inches Minimum And 0.204 Inches Maximum
Head Style:	Round
Head Diameter:	0.193 Inches Minimum And 0.211 Inches Maximum
Head Height:	0.075 Inches Minimum And 0.086 Inches Maximum
Pilot Diameter:	0.092 Inches Minimum And 0.096 Inches Maximum
Pilot Length:	0.047 Inches Nominal
End Item Identification:	W/s:vehicle, Aircraft Refueler R-14; Aircraft, Galaxy C-5; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Support Equipment, B-1 Aircraft; Missile, Air-to-air, Phoenix (aim-54); Torpedo, Mk 48; Missile, All-weather Anti-ship, Harpoon (agm-84); Close In Weapon System (ciws-phalanx); Missile Air-to-air, Sparrow (aim-7); Ground Mobile Force Satellite Comm Term (an/tsc-85a);2320-01-097-0260 Hemtt (heavy Expanded Mobility Tactical Trucks)
Features Provided:	Casehardened
Nonmachine Thread Style:	Drive Screw (type U)
Nonmachine Nominal Thread Diameter:	0.114 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Nondefinitive Spec/std Data:	U Type

How to Order

Order this drive screw from our inventory online by visiting <https://military-fasteners.com/screws/drive+screws/MS21318-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.